


## Application Data Sheet: **D-GREASE**

### D-WAX ALKALINE CLEANER

---



#### **APPLICATION:**

- **ALWAYS TEST PRODUCT ON A SMALL AREA FIRST** for suitability on surface. Pour small amount of D-GREASE on an inconspicuous area and leave for 30mins. Check for any surface damage or any other adverse reactions.
- Sweep or vacuum area to remove all dirt and loose debris.
- With a clean rag, sponge or mop, apply the solution to the surface leaving it to work for a few minutes. A stronger dilution may be used for problem spots.
- When stripping polishes and waxes allow up to 10 minutes for the cleaner to work.
- Agitate with scrubbing brush, pad or floor washing machine where necessary to remove heavy dirt and stains.
- Pick up dirty cleaning water and rinse with clean water. Allow to dry.
- GENERAL cleaning dilute 1 part **D-GREASE** to 100 parts water.
- GREASY areas such as kitchens and for cleaning prior to sealing, dilute 1 part **D-GREASE** to 25 parts water. (Allow 24 hours before sealing with any SOLUTIONS – Sealers products).
- Stripping waxes, polishes or sealers, dilute 1 part **D-GREASE** up to 5 parts water. (You may need to apply neat on SOME waxes - TEST area first).

---

#### **WARNING:**

**D-GREASE** is a high alkaline cleaner and will strip painted surfaces. Also, **D-GREASE** will damage sealed surfaces when used neat or as your primary cleaning agent. For this, we recommend using SOLUTIONS – Sealers **NATURAL CLEAN**.

*Follow safety instructions on label when using D-GREASE.*

---

#### *Disclaimer – User Guide*


*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions – Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions – Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions – Sealers obligations shall be limited to only replacing product PROVEN defective. The user **MUST** educate themselves on the performance value, application rates, substrate type and environment before product is applied, a TEST area is always highly recommended.*

## Technical Data Sheet:

# D-GREASE

## D-WAX ALKALINE CLEANER

---



### Description:

**D-GREASE** is an industrial strength, heavy duty alkaline cleaner specifically designed for cleaning grease, oily areas and stripping waxes and polishes.

---

### Advantages:

- Ideal for removing waxes from porcelain tiles
  - Powerful remover of difficult stains
  - Dissolves heavy greases, oils and built-up grime
  - Excellent for glazed or unglazed ceramic tiles
  - Highly concentrated for industry or commercial use
  - Ideal for cleaning tiles prior sealing
  - Used to neutralize acid washed surfaces
  - Low foaming formula suitable for both machine and manual use
- 

### Characteristics:

Colour:	Clear
Weight:	1.08
DG Class:	8
U.N Number	1760

---

### Recommendations:

Glazed Tiles  
Unglazed Tiles  
Unsealed Tiles  
Unsealed Masonry

---

#### Disclaimer / User Guide

*Solutions - Sealers for Stone & Tile believes the information contained in this document is accurate as **general advice only**. As general advice only it has been prepared without taking into account the objectives, problems or needs of the reader. Solutions . Sealers for Stone & Tile has presented this information as a guide only and accepts no liability for any loss or damage caused by any error in, or omission from, this document. Solutions . Sealers for Stone & Tile has no control over the use or misuse of this product, therefore no warranty expressed or implied shall be given. Solutions . Sealers obligations shall be limited to only replacing product PROVEN defective. The user **MUST** educate themselves on the performance value, application rates, substrate type and environment before product is applied, a **TEST** area is always highly recommended.*